

Data Sheet | Flyscreen Door Sprinter | Crafter

DESCRIPTION

Semi-assembled pleated flyscreen door for installation inside sliding side door openings of Sprinter and derived Crafter (2007-2017) campervans.



OPERATION

Manual step-less adjustment. Closing from right to left (as seen from the inside) for left-hand steered vehicles, optionally from left to right for right-hand steered vehicles

STANDARD DIMENSIONS

Top guider profile length 1,234 mm Bottom guider profile length 1,301 mm Overall height 1,959 mm

Disclaimer | The specifications in this data sheet are for information purposes only and may be subject to change without prior notice © Horrex 2021

MATERIAL SPECIFICATIONS

Top guider profile

Extruded aluminium 24.5 x 23.5 mm (WxH) in light grey (± RAL7047) or optional dark grey (± RAL7021) powder coat (conditions apply)

Pull bar

Extruded aluminium 50 x 17 mm (WxH) in light grey (± RAL7047) or optional dark grey (± RAL7021) powder coat (conditions apply)

Bottom guiding profile

Extruded anodized aluminium (WxH) Sprinter | Crafter (2007-2017) 45 x 16 mm Sprinter (from 2018 onwards) 45 x 18 mm

Side panel (optional)

Black ABS panel, straight for customisation or pre-shaped, aligned with the bodywork and/or interior of the van, for effective protection against insects (conditions apply)

Corner pieces and caps

Colour coordinated injection moulded parts in PA6 and PA6.6

Insect screen mesh

Single pleat black polyester mesh 1.3×1.3 mm (mesh opening), optional FR under standard FMVSS/CMVSS 302 (conditions apply)

INSTALLATION

On- face fixation on the inside with 4 clips underneath the door rubber at the top and 3 screws at the bottom. The required mounting space between door rubber and top cabinet is 27 mm, between door and kitchen cabinet 20 mm and 40 mm for the bottom guiding profile

CLEANING

A soft damp cloth with mild detergent

PACKAGING

Individually or bulk with mounting set

SPECIAL NOTE

Combine a flyscreen door with genuine Horrex UCS combi-blinds







